

POLIDENT CASTING CAD / CAM DISC

POLIDENT CASTING CAD / CAM discs can be used for milling castable frameworks for metal casting and castable layers for press ceramic.

INDICATIONS	CHARACTERISTICS
- Milling frameworks for casting - Milling castable layers for press ceramic - Verifying frameworks on plaster model before final ZrO₂ milling (especially recommended for larger ZrO₂ frameworks)	Produced of 100% organic material that burns-out without any residual ash. Diameter: 95 – 105 mm. Thickness: 12 – 25 mm. Colour: Transparent

Store in dry place at room temperature.

Version: 5.4.2022
No.: 0200215



Polident d.o.o. Slovenija, Volčja Draga 42,
5293 Volčja Draga, Slovenija
T:+386 53304840, F:+386 53304870
E-mail: polident@polident.si

POLIDENT CASTING CAD / CAM DISC

POLIDENT CASTING CAD / CAM discs can be used for milling castable frameworks for metal casting and castable layers for press ceramic.

INDICATIONS	CHARACTERISTICS
- Milling frameworks for casting - Milling castable layers for press ceramic - Verifying frameworks on plaster model before final ZrO₂ milling (especially recommended for larger ZrO₂ frameworks)	Produced of 100% organic material that burns-out without any residual ash. Diameter: 95 – 105 mm. Thickness: 12 – 25 mm. Colour: Transparent

Store in dry place at room temperature.

Version: 5.4.2022
No.: 0200215



Polident d.o.o. Slovenija, Volčja Draga 42,
5293 Volčja Draga, Slovenija
T:+386 53304840, F:+386 53304870
E-mail: polident@polident.si

POLIDENT CASTING CAD / CAM DISC

POLIDENT CASTING CAD / CAM discs can be used for milling castable frameworks for metal casting and castable layers for press ceramic.

INDICATIONS	CHARACTERISTICS
- Milling frameworks for casting - Milling castable layers for press ceramic - Verifying frameworks on plaster model before final ZrO₂ milling (especially recommended for larger ZrO₂ frameworks)	Produced of 100% organic material that burns-out without any residual ash. Diameter: 95 – 105 mm. Thickness: 12 – 25 mm. Colour: Transparent

Store in dry place at room temperature.

Version: 5.4.2022
No.: 0200215



Polident d.o.o. Slovenija, Volčja Draga 42,
5293 Volčja Draga, Slovenija
T:+386 53304840, F:+386 53304870
E-mail: polident@polident.si