PoliDent

according to Regulation (EC) No 1907/2006 (REACH) as amended - COMMISSION REGULATION (EU) 2020/878

0

POLIREPAR S LIQUID

Creation date 14th May 2021

Revision date 23rd December 2022 Version 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier POLIREPAR S LIQUID

Substance / mixture mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Mixture's intended use

Material for the fabrication of dental prosthesis repairs.

Mixture uses advised against

The product should not be used in ways other then those referred in Section 1.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Name or trade name Polident d.o.o., Dental Products

Industry

Address Volčja Draga 42, Volčja Draga, 5293

Slovenia

VAT Reg No SI31319297

Phone 00386 5 3304840, Fax: 00386 5 3304870

E-mail polident@polident.si

Competent person responsible for the safety data sheet

Name Polident d.o.o., Dental Products

Industry

E-mail polident@polident.si

1.4. Emergency telephone number

00386 5 3304840 - Polident d.o.o. - Available from Mon to Fri 7 a.m. to 3 p.m.

112 - Information center - available 0-24

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Eye Irrit. 2, H319 STOT SE 3, H335

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Highly flammable liquid and vapour.

Most serious adverse effects on human health and the environment

Causes skin irritation. May cause respiratory irritation. May cause an allergic skin reaction. Causes serious eye irritation.

2.2. Label elements

Hazard pictogram



Signal word

Danger

Page 1/16 Document: NAV-VL-08



according to Regulation (EC) No 1907/2006 (REACH) as amended - COMMISSION REGULATION (EU) 2020/878

6

POLIREPAR S LIQUID

Creation date 14th May 2021

Revision date 23rd December 2022 Version 3.0

Hazardous substances

Methyl methacrylate

1,4-Butanediol dimethacrylate

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P262 Do not get in eyes, on skin, or on clothing.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.

P501 Dispose of contents/container to in accordance with local/regional/national/international regulations.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Product contents methyl methacrylate, dimethacrylate and activator.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 607-035-00-6 CAS: 80-62-6 EC: 201-297-1 Registration number: 01-2119452498-28	Methyl methacrylate	85-99	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335	1
CAS: 2082-81-7 EC: 218-218-1 Registration number: 01-2119967415-30	1,4-Butanediol dimethacrylate	≤2	Skin Sens. 1B, H317	
EC: 911-490-9 Registration number: 01-2119979579-10- 0001	Reaction mass of 2,2'-[(4-methylphenyl) imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl) amino]-	≤2	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Chronic 3, H412	

Notes

1 A substance for which exposure limits are set.

Full text of all classifications and hazard statements is given in the section 16.

Page 2/16 Document: NAV-VL-08

PoliDent

according to Regulation (EC) No 1907/2006 (REACH) as amended - COMMISSION REGULATION (EU) 2020/878

6

POLIREPAR S LIQUID

Creation date 14th May 2021

Revision date 23rd December 2022 Version 3.0

SECTION 4: First aid measures

4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

Rinse out the mouth with water and provide 2-5 dL of water. Provide medical treatment if the person has any health problems.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

May cause respiratory irritation. Cough, headache.

If on skin

May cause an allergic skin reaction. Irritation, itching, redness.

If in eyes

Causes serious eye irritation. Irritation, lacrimation, pain.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

Highly flammable liquid. In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Highly flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

Page 3/16 Document: NAV-VL-08

PoliDent

according to Regulation (EC) No 1907/2006 (REACH) as amended - COMMISSION REGULATION (EU) 2020/878

6

POLIREPAR S LIQUID

Creation date 14th May 2021

Revision date 23rd December 2022 Version 3.0

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water. In the event of substantial pollution, contact respective authorities and wastewater treatment plants.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Only adequate trained persons may deal with product. For use in dentistry only.

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. The vapour is heavier than air; beware of pits and confined spaces. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. No smoking. Wash hands and exposed parts of the body thoroughly after handling. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges. Keep away from children.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Keep cool. Keep away from sources of ignition - No Smoking. Keep away from children.

Keep the liquid only in the original vessel at a temperature preferably not exceeding 25°C.

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3. Specific end use(s)

Expiry date: Considering the instructions for safety storage and handling the expiry date is three years.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Commission Directive 2009/161/EU

Substance name (component)	Туре	Value	Note
	OEL 8 hours	50 ppm	
Methyl methacrylate (CAS: 80-62-6)	OEL 15 minutes	100 ppm	

Slovenia

Uradni list RS, Št. 72/2021

Substance name (component)	Туре	Value	Note
	8 hours	210 mg/m³	
Methyl methacrylate (CAS: 80-62-6)	8 hours	50 ppm	Substances representing no risk to the foetus with reference to the limit values.
	KTV (15 min)	420 mg/m³	

Page 4/16 Document: NAV-VL-08



according to Regulation (EC) No 1907/2006 (REACH) as amended - COMMISSION REGULATION (EU) 2020/878

6

POLIREPAR S LIQUID

Creation date 14th May 2021

Revision date 23rd December 2022 Version 3.0

Slovenia

Uradni list RS, Št. 72/2021

Substance name (component)	Туре	Value	Note
Methyl methacrylate (CAS: 80-62-6)	KTV (15 min)		Substances representing no risk to the foetus with reference to the limit values.

United Kingdom

EH40/2005 Workplace exposure limits (Fourth Edition 2020)

	- 1		
Substance name (component)	Туре	Value	Note
	WEL 8h	208 mg/m ³	
Mathyd matha andata (CAC, 90, 63, 6)	WEL 8h	50 ppm	
Methyl methacrylate (CAS: 80-62-6)	WEL 15min	416 mg/m ³	
	WEL 15min	100 ppm	

DNEL

1,4-Butanediol dimethacrylate

Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	14.5 mg/m ³	Systemic chronic effects		ECHA REACH
Workers	Dermal	4.2 mg/kg bw/day	Systemic chronic effects		ECHA REACH
Consumers	Inhalation	4.3 mg/m ³	Systemic chronic effects		ECHA REACH
Consumers	Dermal	2.5 mg/kg bw/day	Systemic chronic effects		ECHA REACH
Consumers	Oral	2.5 mg/kg bw/day	Systemic chronic effects		ECHA REACH

Methyl methacrylate

Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	348.4 mg/m ³	Systemic chronic effects		ECHA REACH
Workers	Inhalation	208 mg/m ³	Local chronic effects		ECHA REACH
Workers	Inhalation	416 mg/m ³	Local acute effects		ECHA REACH
Workers	Dermal	13.67 mg/kg bw/day	Systemic chronic effects		ECHA REACH
Workers	Dermal	1.5 mg/cm ²	Local chronic effects		ECHA REACH
Workers	Dermal	1.5 mg/cm ²	Local acute effects		ECHA REACH
Consumers	Inhalation	74.3 mg/m ³	Systemic chronic effects		ECHA REACH
Consumers	Inhalation	104 mg/m ³	Local chronic effects		ECHA REACH
Consumers	Inhalation	208 mg/m ³	Local acute effects		ECHA REACH
Consumers	Dermal	8.2 mg/kg bw/day	Systemic chronic effects		ECHA REACH
Consumers	Dermal	1.5 mg/cm ²	Local chronic effects		ECHA REACH
Consumers	Dermal	1.5 mg/cm ²	Local acute effects		ECHA REACH
Consumers	Oral	8.2 mg/kg bw/day	Systemic chronic effects		ECHA REACH

Page 5/16 Document: NAV-VL-08



according to Regulation (EC) No 1907/2006 (REACH) as amended - COMMISSION REGULATION (EU) 2020/878

6

POLIREPAR S LIQUID

Creation date 14th May 2021

Revision date 23rd December 2022 Version 3.0

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-

Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	9.8 mg/m ³	Systemic chronic effects		ECHA REACH
Workers	Dermal	1.4 mg/kg bw/day	Systemic chronic effects		ECHA REACH
Consumers	Inhalation	1.74 mg/m³	Systemic chronic effects		ECHA REACH
Consumers	Dermal	0.5 mg/kg bw/day	Systemic chronic effects		ECHA REACH
Consumers	Oral	0.5 mg/kg bw/day	Systemic chronic effects		ECHA REACH

PNEC

1,4-Butanediol dimethacrylate

Route of exposure	Value	Value determination	Source
Freshwater environment	0.043 mg/l		ECHA REACH
Seawater	0.004 mg/l		ECHA REACH
Microorganisms in wastewater treatment plants	20 mg/l		ECHA REACH
Freshwater sediment	3.12 mg/kg of dry substance of sediment		ECHA REACH
Freshwater sediment	0.312 mg/kg of dry substance of sediment		ECHA REACH
Soil (agricultural)	0.573 mg/kg of dry substance of soil		ECHA REACH

Methyl methacrylate

Route of exposure	Value	Value determination	Source
Freshwater environment	0.94 mg/l		ECHA REACH
Seawater	0.094 mg/l		ECHA REACH
Microorganisms in wastewater treatment plants	10 mg/l		ECHA REACH
Freshwater sediment	10.2 mg/kg of dry substance of sediment		ECHA REACH
Sea sediments	1.02 mg/kg of dry substance of sediment		ECHA REACH
Soil (agricultural)	1.48 mg/kg of dry substance of soil		ECHA REACH

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-

Route of exposure	Value	Value determination	Source
Freshwater environment	0.048 mg/l		ECHA REACH
Water (intermittent release)	0.48 mg/l		ECHA REACH
Seawater	0.005 mg/l		ECHA REACH
Microorganisms in wastewater treatment plants	10 mg/l		ECHA REACH

Page 6/16 Document: NAV-VL-08



according to Regulation (EC) No 1907/2006 (REACH) as amended - COMMISSION REGULATION (EU) 2020/878

6

POLIREPAR S LIQUID

Creation date 14th May 2021

Revision date 23rd December 2022 Version 3.0

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-

Route of exposure	Value	Value determination	Source
Freshwater sediment	1.2 mg/kg of dry substance of sediment		ECHA REACH
Sea sediments	0.12 mg/kg of dry substance of sediment		ECHA REACH
Soil (agricultural)	0.21 mg/kg of dry substance of soil		ECHA REACH

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective glasses with side shields. EN166 - Personal Eye Protection Standard.

Skin protection

Hand protection: Protective gloves resistant to the product. EN ISO 374-1.

Material: butyl rubber.

Change gloves, if contamination occurs or duration of activity exceed break through time. Breakthrough time of the glove material: refer to the information provided by the glove's producer. Commercial medical gloves do not provide protection against the sensitizing effect of methacrylates. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer.

Respiratory protection

Halfmask with a filter against organic vapours type A or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state liquid Colour colourless

Odour characteristic, strong

Melting point/freezing point -48 °C
Boiling point or initial boiling point and boiling range 100,5 °C

Flammability data not available

Lower and upper explosion limit

bottom 2,1 % upper 12,5 % Flash point 10 °C Auto-ignition temperature 421 °C

Decomposition temperature data not available pH data not available Kinematic viscosity data not available

Viscosity 0,53 mPas at 20 °C
Solubility in water slightly soluble; 1,6 % at 20 °C
1,4-Butanediol dimethacrylate (CAS: 2082-81-7) 243 mg/l (20 °C) (OECD 105)

Partition coefficient n-octanol/water (log value) 1,38

Vapour pressure 3600 Pa at 20 °C

Page 7/16 Document: NAV-VL-08

according to Regulation (EC) No 1907/2006 (REACH) as amended -COMMISSION REGULATION (EU) 2020/878

POLIREPAR S LIQUID

Creation date 14th May 2021

Revision date 23rd December 2022 3.0

Density and/or relative density

Density

0,94 g/cm3 at 20 °C Relative vapour density 3,5 (air = 1)Particle characteristics data not available

9.2. Other information

not available

SECTION 10: Stability and reactivity

10.1. Reactivity

Will exotermically polymerise in the presence of initiators.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Susceptible to polymerisation initiated by prolonged heating or the presence of catalyst.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Polymerisation catalysts, such as peroxy or azo compounds, strong acids, alkalies and oxidizing agents. Oxides and salts of transition metals. Organic Nitrogen containing compounds. Cyclohexanone / Cyclohexenol tautomer.

Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

Acute toxicity

Based on available data the classification criteria are not met.

1,4-Butanediol dimethacrylate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD50	OECD 401	>5000 mg/kg		Rat	
Dermal	LD50		>3000 mg/kg		Rabbit	

Methyl methacrylate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD50		>5000 mg/kg			
Inhalation	LC50		7093 ppm	4 hour		
Dermal	LD50		>5000 mg/kg			

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4methylphenyl)amino]-

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	EC50	OECD 401	619 mg/kg			
Dermal	EC50	OECD 402	>2000 mg/kg			

Document: NAV-VL-08 Page 8/16

PoliDent

according to Regulation (EC) No 1907/2006 (REACH) as amended - COMMISSION REGULATION (EU) 2020/878

6

POLIREPAR S LIQUID

Creation date 14th May 2021

Revision date 23rd December 2022 Version 3.0

Skin corrosion/irritation

Causes skin irritation.

1,4-Butanediol dimethacrylate

Route of exposure	Result	Method	Exposure time	Species	Source
Dermal	Not irritating		24 hour	Rabbit	FDA 1959 Draize

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-

Route of exposure	Result	Method	Exposure time	Species	Source
Dermal	Irritating	OECD 439			
Eye	Irritating	OECD 405			

Serious eye damage/irritation

Causes serious eye irritation.

1,4-Butanediol dimethacrylate

Route of exposure	Result	Method	Exposure time	Species	Source
Eye	Not irritating	OECD 405		Rabbit	FDA 1959 Draize

Methyl methacrylate

Route of exposure	Result	Method	Exposure time	Species	Source
Eye	Slightly irritating	OECD 405		Rabbit	

Respiratory or skin sensitisation

May cause an allergic skin reaction. Repeated and/or prolonged contact may cause dermatitis. Not a respiratory sensitizer.

1,4-Butanediol dimethacrylate

Route of exposure	Result	Method	Exposure time	Species	Sex
Dermal	Sensitizing	OECD 429		Mouse	
Methyl methacrylat	е				

Route of exposure	Result	Method	Exposure time	Species	Sex
Dermal	Sensitizing	OECD 429		Mouse	
Dermal	Sensitizing			Human	

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-

	=				
Route of exposure	Result	Method	Exposure time	Species	Sex
Dermal	Sensitizing	OECD 429			

Mutagenicity

1,4-Butanediol dimethacrylate

Result	Exposure time	Specific target organ	Species	Sex
Negative				

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Methyl methacrylate

Result	Method	Exposure time	Specific target organ	Species	Sex	Source
Negative	OECD 471			Salmonella typhimurium		TA1535, 1537, 97, 98, 100

Page 9/16 Document: NAV-VL-08



according to Regulation (EC) No 1907/2006 (REACH) as amended - COMMISSION REGULATION (EU) 2020/878

0

POLIREPAR S LIQUID

Creation date 14th May 2021

Revision date 23rd December 2022 Version 3.0

Methyl methacrylate

Result	Method	Exposure time	Specific target organ	Species	Sex	Source
Negative	OECD 478					Rodent dominant lethal test
Negative	OECD 474			mammalian erythrocyte micronucleus		in vivo
Positive	OECD 473					In vitro mammali an cell gene mutation test

Carcinogenicity

Based on available data the classification criteria are not met.

1,4-Butanediol dimethacrylate

Route of exposure	Parameter	Method	Value	Result	Species	Sex		
				Negative				
Methyl methacrylate								
Route of exposure	Parameter	Method	Value	Result	Species	Sex		

Not

Result

carcinogenic

Species

Sex

Source

Reproductive toxicity

Effect

I toxicity

Based on available data the classification criteria are not met.

Method

OECD 451

1,4-Butanediol dimethacrylate

Parameter

				Negative				
Methyl methacrylate								
Effect	Parameter	Method	Value	Result	Species	Sex	Source	
Effects on fertility	NOAEC	OECD 414	>2028 ppm		Rat		vdihavanje	
Developmenta	NOAEL		450 mg/kg bw		Rabbit		oralno	

Toxicity for specific target organ - single exposure

May cause respiratory irritation.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Repeated exposure to high levels produces adverse effects on the heart, lungs, liver and kidneys.

Value

Repeated exposure of animals by inhalation to levels at or above the occupational exposure level produces adverse effects on the nasal epithelium (levels of 100 and 400 ppm).

There is no reason to believe that methyl methacrylate represents a carcinogenic or mutagenic hazard to man based upon evidence from well conducted animal studies, relevant mutagenicity studies and adequate epidemiology studies in relevant cohorts.

Recent studies in animals have shown that high exposures do not produce embryo or foetotoxic nor teratogenic effects in the presence of maternal toxicity.

1,4-Butanediol dimethacrylate

Route of exposure	Parameter	Method	Value	Exposure time	Result	Species	Sex
Oral		OECD 422	300 mg/kg			Rat	

Page 10/16 Document: NAV-VL-08



according to Regulation (EC) No 1907/2006 (REACH) as amended - COMMISSION REGULATION (EU) 2020/878

6

POLIREPAR S LIQUID

Creation date 14th May 2021

Revision date 23rd December 2022 Version 3.0

Methyl methacrylate

Route of exposure	Parameter	Method	Value	Exposure time	Result	Species	Sex
Oral	NOEL		>2000 ppm	104 week		Rat	
Inhalation	NOAEC	OECD 453	100 ppm	104 week		Rat	
Inhalation	NOAEC	OECD 412	1000 ppm	14 week		Mouse	

Aspiration hazard

Based on available data the classification criteria are not met.

11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity

It can cause harmful effects on the environment. Prevent uncontrolled release.

1,4-Butanediol dimethacrylate

Parameter	Method	Value	Exposure time	Species	Environm ent	Value determination	Source
LC50		32.5 mg/l	48 hour	Fishes (Leuciscus idus)			DIN 38412 - 15
EC50	OECD 201	9.79 mg/l	72 hour	Algae (Desmodesmus subspicatus)			
EC 10	OECD 201	4.35 mg/l	72 hour	Algae (Desmodesmus subspicatus)			
NOEC		20 mg/l		Microorganisms			

Methyl methacrylate

Parameter	Method	Value	Exposure time	Species	Environm ent	Value determination	Source
LC50		>100 mg/l		Fishes			
LC50		130 mg/l	96 hour	Fishes (Fathead minnow)		Static system	
EC50		69 mg/l	48 hour	Daphnia (Daphnia magna)			
EC50		170 mg/l	96 hour	Algae (Selenastrum capricornutum)			

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-

metry pheny () drinnoj									
Parameter	Method	Value	Exposure time	Species	Environm ent	Value determination	Source		
LC50	OECD 203	>100 mg/l	96 hour	Fishes (Oncorhynchus mykiss)					
EC ₅ 0	OECD 202	48 mg/l	48 hour	Daphnia (Daphnia magna)					
EC ₅ 0	OECD 201	>100 mg/l		Algae (Selenastrum capricornutum)					

Page 11/16 Document: NAV-VL-08

PoliDent

according to Regulation (EC) No 1907/2006 (REACH) as amended - COMMISSION REGULATION (EU) 2020/878

0

POLIREPAR S LIQUID

Creation date 14th May 2021

Revision date 23rd December 2022 Version 3.0

Chronic toxicity

1,4-Butanediol dimethacrylate

Parameter	Method	Value	Exposure time	Species	Environmen t
EC 10	OECD 211	7.51 mg/l	21 day	Daphnia (Daphnia magna)	

Methyl methacrylate

Parameter	Method	Value	Exposure time	Species	Environmen t
NOEC		8.4 mg/l	35 day	Fishes (Zebra fish)	

12.2. Persistence and degradability

Biodegradability

1,4-Butanediol dimethacrylate

Parameter	Method	Value	Exposure time	Environment	Result
	OECD 310	84 %	28 day		Biodegradable

Methyl methacrylate

Parameter	Method	Value	Exposure time	Environment	Result
					Easily biodegradable
COD		88 %	28 day		
DOC removal		>95 %	28 day		

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-

Parameter	Method	Value	Exposure time	Environment	Result
	OECD 301B	>100 mg/l	96 hour		Hardly biodegradable

Readily biodegradable.

12.3. Bioaccumulative potential

1,4-Butanediol dimethacrylate

Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]
Log Pow	OECD 117	3.1				

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-

Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]
Log Kow	OECD 117	2.17				

The product has low potential for bioacumulation.

12.4. Mobility in soil

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-

Parameter	Method	Value	Environment	Temperature
Log Koc	OECD 122	2.33		20°C

The product is predicted to have high mobility in soil.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Not available.

Page 12/16 Document: NAV-VL-08

PoliDent

according to Regulation (EC) No 1907/2006 (REACH) as amended - COMMISSION REGULATION (EU) 2020/878

6

POLIREPAR S LIQUID

Creation date 14th May 2021

Revision date 23rd December 2022 Version 3.0

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Producer Responsibility Obligations (Packaging Waste) Regulations 2007 (S.I. No. 871 of 2007). Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1247

14.2. UN proper shipping name

METHYL METHACRYLATE MONOMER, STABILIZED

14.3. Transport hazard class(es)

3 Flammable liquids

14.4. Packing group

II - substances presenting medium danger

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Always transport closed containers in the upright position. Make sure that the person transporting the product knows the ways of handling the product in the event of accident. Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

Additional information

Hazard identification No.

UN number

Classification code

Safety signs

339 1247

F1



Page 13/16 Document: NAV-VL-08



according to Regulation (EC) No 1907/2006 (REACH) as amended - COMMISSION REGULATION (EU) 2020/878

0

POLIREPAR S LIQUID

Creation date 14th May 2021

Revision date 23rd December 2022 Version 3.0

Road transport - ADR

Special provisions 386
Limited quantities 1 L
Excepted quantities E2

Packaging

Packing instructions P001, IBC02, R001

Mixed packing provisions MP19

Portable tanks and bulk containers

Guidelines T4
Special provisions TP1

ADR tank

Tank code LGBF
Vehicles for tank carriage FL
Transport category 2
Tunnel restriction code (D/E)

Special provision for

packages V8

operation S2, S4, S20

Railway transport - RID

Special provisions 386 Excepted quantities E2

Packaging

Packing instructions P001, IBC02, R001

Mixed packing provisions MP19

Portable tanks and bulk containers

Guidelines T4
Special provisions TP1

RID Tanks

Tank code LGBF Transport category 0

Special provision for

packages W 8

Air transport - ICAO/IATA

Packaging instructions for limited amount Y341
Packaging instructions passenger 353
Cargo packaging instructions 364

Marine transport - IMDG

EmS (emergency plan) F-E, S-D

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 as amended. Environmental Protection Act 1990 as amended. Clean Air Act 1993 as amended. Public health act 1961. Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended.

Product is a medical device class IIa according to the Medical Device Regulation MDR 2017/745.

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

Page 14/16 Document: NAV-VL-08



according to Regulation (EC) No 1907/2006 (REACH) as amended - COMMISSION REGULATION (EU) 2020/878

0

POLIREPAR S LIQUID

Creation date 14th May 2021
Revision date 23rd December 2022

rsion 3.0

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.

P501 Dispose of contents/container to in accordance with

local/regional/national/international regulations.

P262 Do not get in eyes, on skin, or on clothing.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR European agreement concerning the international carriage of dangerous goods by

road

BCF Bioconcentration Factor
CAS Chemical Abstracts Service

CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of

substance and mixtures

DNEL Derived no-effect level

EC Identification code for each substance listed in EINECS

EC50 Concentration of a substance when it is affected 50% of the population EINECS European Inventory of Existing Commercial Chemical Substances

EmS Emergency plan EU European Union

EuPCS European Product Categorisation System IATA International Air Transport Association

IBC International Code For The Construction And Equipment of Ships Carrying

Dangerous Chemicals

ICAO International Civil Aviation Organization IMDG International Maritime Dangerous Goods

INCI International Nomenclature of Cosmetic Ingredients
ISO International Organization for Standardization
IUPAC International Union of Pure and Applied Chemistry

LC50 Lethal concentration of a substance in which it can be expected death of 50% of the

population

LD50 Lethal dose of a substance in which it can be expected death of 50% of the

population

log Kow Octanol-water partition coefficient

MARPOL International Convention for the Prevention of Pollution from Ships

NOAEC No observed adverse effect concentration

NOAEL No observed adverse effect level NOEC No observed effect concentration

NOEL No observed effect level
OEL Occupational Exposure Limits

Page 15/16 Document: NAV-VL-08



according to Regulation (EC) No 1907/2006 (REACH) as amended - COMMISSION REGULATION (EU) 2020/878

6

POLIREPAR S LIQUID

Creation date 14th May 2021
Revision date 23rd December 2022 Version 3.0

PBT Persistent, Bioaccumulative and Toxic
PNEC Predicted no-effect concentration

ppm Parts per million

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Agreement on the transport of dangerous goods by rail

UN Four-figure identification number of the substance or article taken from the UN

Model Regulations

UVCB Substances of unknown or variable composition, complex reaction products or

biological materials

VOC Volatile organic compounds

vPvB Very Persistent and very Bioaccumulative

Acute Tox. Acute toxicity

Aquatic Chronic Hazardous to the aquatic environment (chronic)

Eye Dam. Serious eye damage

Eye Irrit.Eye irritationFlam. Liq.Flammable liquidSkin Irrit.Skin irritationSkin Sens.Skin sensitization

STOT SE Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 3.0 replaces the SDS version 2.0. and first version from 14.05.2021.

Changes were made in sections:

- 2.1 Classification of the substance or mixture,
- 2.2 Label elements,
- 2.3 Other hazards,
- 3.2 Mixtures content in % weight,
- 11.2 Information on other hazards,
- 12.6 Endocrine disrupting properties and
- 16 Other information.

More information

 ${\it Classification\ procedure\ -\ calculation\ method.}$

Safety Data Sheet created by CHEM CONSULTING s.p.(www.chem-consulting.si)

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.

Page 16/16 Document: NAV-VL-08